

METRYKA OTWORU WYKONANGO

ŚWUAEM RAŻNYM NR..»f-

VuM.MKttaMMeJ^ WKaXWWCJiiiUi.-:JeyMt^KAt^JLUKSM/^.-.-^Dltav^aiwm...^a&Mei^-

WąwiMte... ^it^O<-«Ł...-...^...-...».....J^^«IA.-i5'<-...-...-WteBWlq^nMŁ...-...-... ,—.....

Ki<^«ei»-w«LB.p.«...fl<M,A<?-.....-...-SBi(p)ii4y..Jifcflfl(<<JM(^.....-... N»*riryot«Amo»ay..-...-.....

l»	•K-rrw		4 t	1	^		ldM(——IN<—			j	/	4 i!]
	ft	>			• • *t- • j	ł							
4.	ao	0.1	0.2	r<			HWUS cwflHo -ffora	^4	U	—	—	/	j ^
Ł.	Q.2	0.6	04	Q*			GIWA ZWfZłA 'DoSciw...Mr»	<-(—'	2	TH.	s.	Są .
5.	~Q.	'i.i	0.6	Qp			6UfiA WASZCZ/STA .J.IQnifi<I^OI	<4	••—	3 ¹	'»i	s.	C 2
4.	f. l	S.l	0.9	Ps.			?/A&E.< \$kt'WI ^ttowir^	<1	M	^H>	—	IT ¹	<
5.	Z.-f	2.9	0.6	fr	W	2.6	f S fiA5FK GkOBY ,,,, ^WTO-7^tH^	<r-	•Hrl	~*~	^	f	^ N
~6	f.ł	S.7	0.6	6r,			C,ilfiA fUASTA WWA f lopti -uara	<1	- -"	"	3	W.	R s s2

Przykładowa metryka otworu wiertniczego